



MODEL SS-50M



Product Data Sheet

SS-50M (IEC 62368)
Switching Power Supply
13.8 VDC, adjustable
50 Amps, peak current

Key Features

- **Connectors:** [AC] IEC320-C14, [DC] 2 USB ports, 2 Anderson Power Pole ports, 1x2-Wire Terminals Rear panel port.
- **Digital Displays:** Front Panel numeric LED, 1 DC Volt meter and 1 Amp meter, Illuminated ON/OFF switch.
- **Adjustable Voltage:** 13.8 VDC $\pm 1V$, User manual control.
- **Technology:** >82% efficiency switching, PFC, specific filtering for communication equipment all frequencies and HF.
- **EMI:** Built-in EMI filter meets EMI Standards, EN55022/CISPR 22 (Class-B), FCC Part15 (Class-B), EN55024, EN61000-3-2 (Class-D), EN61000-3-3 (Harmonic) IEC61000-4-2,4,5 (EMS).
- **Protections Built-in:** Current Limiting, Overvoltage protection, Fuse protection, Over Temperature shutdown.
- **Construction:** Low profile, light weight and industrial metal case quality. Optional rack-mount front panel is available.
- **Safety:** Certified to UL/CUL/EN/IEC 62368-1 standards.
- **Environmental:** Certified to Energy Star and CEC standards where required, and RoHS (lead free) compliant.

Applications

Communications Equipment - A Critical Power Solution

The SS-50M model supports currents up to 40A avg and peak up to 50A ICS (*) peak max. It is ideally suited for use with 12/13.8 VDC communications equipment. Switching technology >82% efficient meets individual power loading requirements. Included is special filter circuitry especially suited for all communications frequencies and HF.

Built-in Protection Features

Several protection features are built-in. Included are output current limiting, overvoltage protection, internal fuse protection, and over temperature shutdown.

Easy installation, safety and reliability

Integration is seamless with standard 12/13.8 VDC equipment. Front panel 'Anderson Power Pole'; terminals and rear panel screw-wire terminals are heavy duty. Connectors are easy accessible which ensures safe and reliable installation.

Specifications

• INPUT VOLTAGE:	120 to 230 VAC, 50/60Hz (Nominal Automatic Wide-Range selected)
• OUTPUT VOLTAGES:	13.8 VDC (User manual adjustable $\pm 1 V$) 2 USB ports: 5.2V, 1.5A per port
• OUTPUT CURRENT	50A peak current - ICS Intermittent Communication Service (*)
• TEMPERATURE	0 to +50°C Operating, -20 to +85°C Storage 120°C max over-temperature setting
• HUMIDITY	5 to 90% RH Operating, 5 to 95% RH Storage (Non-condensing)

Model No.	Voltage Input	Voltage Output	Amps Output	Case: (H x W x D)
SS-50M	Nominal Auto Selected 120 to 230 VAC 50/60Hz	User Manual Adjust $\pm 1V$ 12.8 to 14.8 VDC $\pm 2\%$	40 A continuous max 50 A peak ICS (*) max	2 ⁵ / ₈ x 7 x 8 ¹ / ₄ in 67.5 x 7 x 207.5 mm



(*) Intermittent Communication Service. Peak current limited to 33% max Duty Cycle, 5 minutes max ON time.



WWW.ASTRONCORP.COM

9 Autry, Irvine, CA 92618 • (949) 458-7277 • Fax: (949) 458-0826